

Channels



Specification

Size	h (mm)	Tolerance	b (mm)	Tolerance	Thickness (mm)	Tolerance	Weight (kg/m)
5#	50	±1.5	37	±1.5	4.5	±0.4	5.438
6.3#	63	±1.5	40	±1.5	4.8	±0.4	6.634
8#	80	±1.5	43	±1.5	5	±0.4	8.045
10#	100	±2.0	48	±2.0	5.3	±0.5	10.007
12#	120	±2.0	53	±2.0	5.5	±0.5	12.059
14A#	140	±2.0	58	±2.0	6.0	±0.5	14.535
14B#	140	±2.0	60	±2.0	8.0	±0.5	16.733
16A#	160	±2.0	63	±2.5	6.5	±0.6	17.24
16B#	160	±2.0	65	±2.5	8.5	±0.6	19.752
18A#	180	±2.0	68	±2.5	7.0	±0.6	20.147
18B#	180	±2.0	70	±2.5	9.0	±0.6	23
20A#	200	±3.0	73	±3.0	7.0	±0.7	22.637
20B#	200	±3.0	75	±3.0	9.0	±0.7	25.777
22A#	220	±3.0	77	±3.0	7.0	±0.7	24.999
22B#	220	±3.0	79	±3.0	9.0	±0.7	28.453
25A#	250	±3.0	78	±3.0	7.0	±0.7	27.41
25B#	250	±3.0	80	±3.0	9.0	±0.7	31.335
28A#	280	±3.0	82	±3.0	7.5	±0.7	31.427
28B#	280	±3.0	84	±3.0	9.5	±0.7	35.823
30A#	300	±3.0	85	±3.0	7.5	±0.7	34.463
30B#	300	±3.0	87	±3.0	9.5	±0.7	39.173
32A#	320	±3.0	88	±3.5	8	±0.8	38.083

Length=6—12meters